


[HD Rubber]
Heavy Duty Rubber Covered Hose



HD 600 is a flexible layflat fire hose designed for industrial fire protection. This third generation product is built from specially formulated synthetic nitrile rubber to produce excellent abrasion resistance. It is highly resistant to fuels, chemicals, oils, heat and environmental pollutants. It is impervious to molds, mildew and other airborne organisms

Dimensions:

Burst, Hydrostatic and Friction Loss Test Data.

Hose shall comply with the requirements listed in the tables below and the requirements of The National Fire Protection Association Standard 1961, 2002 Edition.

Sizes & Pressures

Size	Bowl Size	Service Pressure	Minimum Burst Pressure
1"	1- 3/16"	300	900 psi
1-1/2"	1-3/4"	300	900 psi
1-3/4"	2"	300	900 psi
2"	2-3/16"	300	900 psi
2-1/2"	2-3/4"	300	900 psi
3"	3-5/16"	300	900 psi

PROJECT	APPROVAL STAMP
PROJECT:	<input type="checkbox"/> APPROVED
ADDRESS:	<input type="checkbox"/> APPROVED AS NOTED
ENGINEER:	<input type="checkbox"/> NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	