

**[ IE2600-15-FF-SS ]**

**1-1/2" Female x Female Factory Set Pressure Reducing Angle Valve with Supervisory Switch**



**INFORMATION**

The Wilson and Cousins' **IE2600-15-FF-SS** Series feature a range of 1-1/2" Female NPT by Female NPT factory set pressure reducing angle valves. These brass valves are intended to serve as floor control valves, standpipe valves, or a checking device. Listed by Underwriters' Laboratories, the **IE2600-15-FF-SS** series can handle FLOW and NO-FLOW conditions, as required by NFPA for CLASS II systems, up to maximum inlet pressures of 400 psi.

The inclusion of a Supervisory Switch allows for external monitoring of the valves Open/Closed position.

Download our Valve Selection Guide from our "SUPPORT" page, to find the recommended valve size for your application.

**OPTIONS**

Chrome Plate Finish

**CONNECTION OPTIONS**

Female NPT x Male Hose (-FM)


Groove x Male Hose (-GM)

Groove x Groove (-GG)

**LISTED**



**Dimensions:**



- A: 9.63" (244mm) [Open]
- A: 9.00" (228mm) [Closed]
- B: 4.38" (111mm)
- C: 1.88" (47mm)
- D: 2.06" (53mm)
- E: 4.56" (116mm)

PROJECT	APPROVAL STAMP
PROJECT:	<input type="checkbox"/> APPROVED
ADDRESS:	<input type="checkbox"/> APPROVED AS NOTED
ENGINEER:	<input type="checkbox"/> NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	