

[IE2600-15-FM-SS]
1-1/2" Female x Male Factory Set Pressure Reducing Angle Valve with Supervisory Switch



INFORMATION

The Wilson and Cousins' **IE2600-15-FM-SS** Series feature a range of 1-1/2" Female NPT by Male hose thread factory set pressure reducing angle valves. These brass valves are intended to serve as floor control valves, standpipe valves, or a checking device. Listed by Underwriters' Laboratories, the **IE2600-15-FM-SS** series can handle FLOW and NO-FLOW conditions, as required by NFPA for CLASS II systems, up to maximum inlet pressures of 400 psi. The inclusion of a Supervisory Switch allows for external monitoring of the valves Open/Closed position.

Download our Valve Selection Guide from our "SUPPORT" page, to find the recommended valve size for your application.

OPTIONS

Chrome Plate Finish


CONNECTION OPTIONS

- Female NPT x Female NPT (-FF)
- Groove x Male Hose (-GM)
- Groove x Groove (-GG)

LISTED



Dimensions:



- A: 9.63" (244mm) [Open]
- A: 9.00" (228mm) [Closed]
- B: 4.38" (111mm)
- C: 1.88" (47mm)
- D: 2.88" (73mm)
- E: 4.56" (116mm)

PROJECT	APPROVAL STAMP
PROJECT:	<input type="checkbox"/> APPROVED
ADDRESS:	<input type="checkbox"/> APPROVED AS NOTED
ENGINEER:	<input type="checkbox"/> NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	