

[IE2600-15-GG-SS]

1-1/2" Groove x Groove Factory Set Pressure Reducing Angle Valve with Supervisory Switch



INFORMATION

The Wilson and Cousins' **IE2600-15-GG-SS** Series feature a range of 1-1/2" Grooved by Grooved factory set pressure reducing angle valves. These brass valves are intended to serve as floor control valves, standpipe valves, or a checking device. Listed by Underwriters' Laboratories, the **IE2600-15-GG-SS** series can handle FLOW and NO-FLOW conditions, as required by NFPA for CLASS II systems, up to maximum inlet pressures of 400 psi.

The inclusion of a Supervisory Switch allows for external monitoring of the valves Open/Closed position.

Download our Valve Selection Guide from our "SUPPORT" page, to find the recommended valve size for your application.

OPTIONS

Chrome Plate Finish

CONNECTION OPTIONS

Female NPT x Female NPT (-FF)


Female NPT x Male Hose (-FM)

Groove x Male Hose (-GM)

LISTED



Dimensions:



A:	10.50"	(267mm)	[Open]
A:	9.88"	(251mm)	[Closed]
B:	4.38"	(111mm)	
C:	2.75"	(70mm)	
D:	2.88"	(73mm)	
E:	4.56"	(116mm)	

PROJECT	APPROVAL STAMP
PROJECT:	<input type="checkbox"/> APPROVED
ADDRESS:	<input type="checkbox"/> APPROVED AS NOTED
ENGINEER:	<input type="checkbox"/> NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	