

**[ IE2600-25-FF-SS ]**  
**2-1/2" Female x Female Factory Set Pressure Reducing Angle Valve with Supervisory Switch**



**INFORMATION**

The Wilson and Cousins' **IE2600-25-FF-SS** Series feature a range of 2-1/2" Female NPT by Female NPT factory set pressure reducing angle valves. These brass valves are intended to serve as floor control valves, standpipe valves, or a checking device. Listed by Underwriters' Laboratories, the **IE2600-25-FF-SS** series can handle FLOW and NO-FLOW conditions, as required by NFPA for CLASS I and III systems, up to maximum inlet pressures of 400 psi. Tapped and plugged holes (1/4") are standard on all bodies to allow for monitoring by external pressure gauges (supplied by others).

The inclusion of a Supervisory Switch allows for external monitoring of the valves Open/Closed position.

Download our Valve Selection Guide from our "SUPPORT" page, to find the recommended valve size for your application.

**OPTIONS**

Chrome Plate Finish


**CONNECTION OPTIONS**

- Female NPT x Male Hose; Angle (-FM)
- Female NPT x Female NPT; Inline (-ST)
- Groove x Male Hose; Angle (-GM)
- Groove x Groove; Angle (-GG)
- Groove x Groove; Inline (-SG)

**LISTED**



**Dimensions:**



- A: 12.69" (322 mm) **[OPEN]**
- A: 11.94" (303 mm) **[CLOSED]**
- B: 2.63" (67 mm)
- C: 3.13" (79 mm)

PROJECT	APPROVAL STAMP
PROJECT:	<input type="checkbox"/> APPROVED
ADDRESS:	<input type="checkbox"/> APPROVED AS NOTED
ENGINEER:	<input type="checkbox"/> NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	