

[IE2600-25-ST-SS]
2-1/2" Female x Female Factory Set Pressure Reducing Inline Valve with Supervisory Switch



INFORMATION

The Wilson and Cousins' **IE2600-25-ST-SS** Series feature a range of 2-1/2" Female NPT by Female NPT factory set pressure reducing inline valves. These brass valves are intended to serve as floor control valves, standpipe valves, or a checking device. Listed by Underwriters' Laboratories, the **IE2600-25-ST-SS** series can handle FLOW and NO-FLOW conditions, as required by NFPA for CLASS I and III systems, up to maximum inlet pressures of 400 psi. Tapped and plugged holes (1/4") are standard on all bodies to allow for monitoring by external pressure gauges (supplied by others).

The inclusion of a Supervisory Switch allows for external monitoring of the valves Open/Closed position.

Download our Valve Selection Guide from our "SUPPORT" page, to find the recommended valve size for your application.

OPTIONS

Chrome Plate Finish


CONNECTION OPTIONS

- Female NPT x Male Hose; Angle (-FM)
- Female NPT x Female NPT; Angle (-FF)
- Groove x Groove; Inline (-SG)
- Groove x Groove; Angle (-GG)
- Groove x Male Hose; Angle (-GM)

LISTED



Dimensions:



- A: 13.38" (340 mm) [OPEN]
- A: 12.63" (321 mm) [CLOSED]
- B: 1.88" (47 mm)
- C: 6.75" (171 mm)

| PROJECT | APPROVAL STAMP |
|-----------------|--|
| PROJECT: | <input type="checkbox"/> APPROVED |
| ADDRESS: | <input type="checkbox"/> APPROVED AS NOTED |
| ENGINEER: | <input type="checkbox"/> NOT APPROVED |
| SUBMITTAL DATA: | REMARKS: |
| NOTES 1: | |
| NOTES 2: | |