

[IE33D-425]

4.0" NPT x (2)2.5" Hose Swivel - Inline Exposed Brass FDC w. Double Drop Clappers



INFORMATION

Wilson and Cousins' **IE33D** is an inline, exposed body, cast brass fire department connection (FDC) featuring a single 4.0" (DN100) outlet and two 2.5" (DN65) hose swivels with dual drop clappers. The IE33D is UL/ULC Listed and FM Approved as an auxiliary connection to allow up to 500 GPM to supplement a system water supply for fire protection. The dual drop clappers provide an unobstructed waterway and the exposed design is an economical method of satisfying fire department inlet requirements. Specify regional hose thread for inlet.

FINISH

Cast Brass

OPTIONAL FINISHES

Cast Chrome or Polish Chrome


AVAILABLE HOSE THREADS

CSA, BCT, WCT, QST, NSST, NPSH, NST, Louisville, Cleveland, Chicago, Pittsburgh, New Cincinnati, New York Corp., New York Fire Department, Richmond and Raleigh

LISTED



Dimensions:



- A:** 10.80" (275 mm)
- B:** 7.20" (182 mm)
- C:** 4.00" NPT
- D:** Subject to hose thread

PROJECT	APPROVAL STAMP
PROJECT:	<input type="checkbox"/> APPROVED
ADDRESS:	<input type="checkbox"/> APPROVED AS NOTED
ENGINEER:	<input type="checkbox"/> NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	