

**[ IE34S PAC BRASS ]**

**4"x2.5"x2.5" Brass angle body exposed fire department connection with brass accessories**



4" (100mm) NPT x 2.5" (65mm) hose thread x 2.5" (65mm) hose thread cast brass angle body exposed fire department connection with brass accessories. The IE34S is a UL / ULC Listed and FM Approved swing clapper body that is used as an auxiliary connection and allows up to 500 GPM to supplement the system water supply for fire protection. The swing clapper provides unobstructed waterway and the exposed design is an economical method of satisfying fire department inlet requirements. The package includes the IE34S body, two brass plugs and chains and a brass round escutcheon plate. There is also the option to add an 18" polish brass sleeve. Specify regional hose thread for outlet.


**FINISH:** Cast Brass

**OPTIONS:** Polish Brass, Cast Chrome or Polish Chrome

**HOSE THREADS AVAILABLE:** CSA, BCT, WCT, QST, NSST, NPSH, NST, Louisville, Cleveland, Chicago, Pittsburgh, New Cincinnati, New York Corp., New York Fire Department, Richmond and Raleigh. Other threads see factory for availability.



**Dimensions:**



- A = 10.25" (260mm)
- B = 4.25" (108mm)
- C = 0.25" (6mm)
- D = 18.25" (464mm)
- E = 21" (533mm)
- F = 22.5" (572mm)

PROJECT	APPROVAL STAMP
PROJECT:	<input type="checkbox"/> APPROVED
ADDRESS:	<input type="checkbox"/> APPROVED AS NOTED
ENGINEER:	<input type="checkbox"/> NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	