


**[ IE7-V5 ]**  
**26" Red Swinging Hose Reel**



The IE7-V5 can hold either 1.5" (38 mm), 2" (51 mm) or 2.5" (65 mm) hose (please see chart below for capacities). The 26" (660 mm) red swinging hose reel is used as an efficient, compact package providing stationary hose storage and easy deployment of collapsible hose. The hose reel is made of Steel Round Bar rims and Steel Flat Bar spokes, and when mounted on the rugged steel brackets can swing out 180 degrees. The open design also helps with faster hose drying after use to prevent mold and mildew. The reel can be used in fire protection or washdown applications.

MODEL	HOSE SIZE INCHES (mm)	RACK HOSE FEET (m)	SINGLE JACKET FEET (m)	DBL JACKET FEET (m)
IE7-24"P	1-1/2 (38)	100 (30.5)	75 (23)	50 (15)
IE7-V5	2 (51) or 2-1/2 (65)	150 (45.7)	100 (30.5)	75 (23)
IE7-V5	1-1/2 (38)	300 (91.4)	200 (61)	150 (45.7)
IE7-V7	2 (51) or 2-1/2 (65)	-	200 (61)	150 (45.7)

**Dimensions:**



- A= 34" (864mm)
- B= 30" (762mm)
- C= 5.5" (140mm)
- D= 9.5" (241mm)
- Reel=26"(660mm)
- F= 13" (330mm)
- G= 2" (50.8mm)

PROJECT	APPROVAL STAMP
PROJECT:	<input type="checkbox"/> APPROVED
ADDRESS:	<input type="checkbox"/> APPROVED AS NOTED
ENGINEER:	<input type="checkbox"/> NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	