

[IE34D-625 HPCP] 6.0" NPT x (2)2.5" Hose Swivel - Angle Exposed HP Chrome FDC w. Double Clappers



INFORMATION

Wilson and Cousins' **IE34**D-**625** HPCP is an angled (90-Degree), exposed body, cast brass, high polish chrome plated fire department connection (FDC) featuring a single 6.0" (DN150) outlet and two 2.5" (DN65) hose swivels with dual drop clappers. The IE34D-625 series are UL/ULC Listed and FM Approved as an auxiliary connection to allow up to 500 GPM to supplement a system water supply for fire protection. The dual drop clappers provide an unobstructed waterway and the exposed design is an economical method of satisfying fire department inlet requirements. Specify regional hose thread for inlet.

FINISH

Polish Chrome

OPTIONAL FINISHES

Cast Brass or Polish Brass

AVAILABLE HOSE THREADS

CSA, BCT, WCT,QST, NSST, NPSH, NST, Louisville, Cleveland, Chicago, Pittsburgh, New Cincinnati, New York Corp., New York Fire Department, Richmond and Raleigh


LISTED








Dimensions:





A: 11.88" (302 mm) **B:** 8.13" (206 mm) **C:** 5.81" (147 mm)

PROJECT	APPROVAL STAMP
PROJECT:	☐ APPROVED
ADDRESS:	☐ APPROVED AS NOTED
ENGINEER:	☐ NOT APPROVED
SUBMITTAL DATA:	REMARKS:
NOTES 1:	
NOTES 2:	